

HDDWMVFIR / HDDWMVFIRW


4-in-1, Full HD 1080p Outdoor IR Eyeball Camera

2.8-12mm, 90' IR Range

FEATURES:

- ♦ Multi Format (TVI, CVI, AHD, 960H)
- ♦ Full HD 1080p Resolution
- ♦ True Day/Night Mechanical IR Cut Filter
- Digital Wide Dynamic Range
- ♦ 3-Axis Wall or Ceiling Mountable
- Sense-up / Slow Shutter Speed
- ◆ UTC & Joystick Controllable OSD
- ♦ 12 Volt DC Power
- ♦ 3D Digital Noise Reduction
- ◆ 18 IR LED's / 90' IR Range
- ♦ 2.8 ~ 12mm Varifocal Lens
- ♦ 1/3" Sony CMOS Sensor
- IP66 Weatherproof

CAMERA OVERVIEW:



& Mounting Configuration


INCLUDED ACCESSORIES:

- 1. Camera
- 1. User Manual
- 1. Mounting Screws

RECOMMENDED ACCESSORIES:







Note: Specification subject to change without notice

DWMVFBBW White Back Box



In-Line Cable Mounted OSD Control





960H ANALOG

SPECIFICATION	HDDWMVFIR	HDDWMVFIRW	
mage Sensor	1/3" Sony CMOS Sensor		
Total Pixels	1984 x 1225		
Active Pixels	1920 x 1080		
Resolution	1920 x 1080 (1080p)		
Scanning System	Progressive Scan		
OSD (On Screen Display)	Dual OSD Access: Cable Mounted Joystick Controlled / UTC Controlled (coaxial control)		
Digital WDR (Wide Dynamic Range)	Auto / Off / On - 0 ~ 8 Adjustable		
DNR (Digital Noise Reduction)	2D & 3D, Low, Middle, High, Off		
Video Output	Dual Pigtail HD-TVI Main Output (yellow) / 960H Secondary Output (black)		
Lens Type - True Day Night	2.8 12mm Varifocal Lens		
Sense-up	Off / x2 ~ x30		
Shutter Speed	Auto, FLK, 1/30 ~ 1/50,000, x2 ~ x30		
IR Cut Filter	Built in Mechanical		
Minimum Illumination	0.0 Lux IR LED On		
IR LED Count / Range	18 IR LED's / 90' Range / 850nM		
S/N Ratio	More than 50dB		
Automatic Gain Control	0 ~100 Adjustable		
Sync System	Internal		
Gamma Characteristics	y = 0.45 typ.		
White Balance	ATW / AWC->Set / Indoor / Outdoor / Manual		
Back Light Compensation	Off / BLC / HSBLC		
HBLC (High Back Light Compensation)	On / Off		
Day/Night	EXT / Auto / Color / B/W		
Mirror	Mirror / V-Flip / Rotate / Off		
Languages	English, French, Spanish, German, Italian (see OSD Menu for more)		
Brightness	0 ~100 Adjustable		
Motion Detection	On/Off (4 Zone Selectable)		
Privacy Mask	On/Off (4 Zone Selectable)		
Power Input	12VDC Only		
Power Requirement	180mA / 550mA IR LED ON		
Overall Camera Dimensions	4.7" x 3.4" (120mm x 88mm)		
Housing / Color	Aluminum - Gray	Aluminum - Gray Aluminum - White	
Weight	1.6 Lb.		
Operating Temperature	-14°F ~ 122°F		
Weatherproof Rating	IP66		