

TEMP°ALERT®

PROTECT PROPERTY FROM THE ADVERSE EFFECTS OF TEMPERATURE EXTREMES



TA-40 (PN 1100)

Low Temperature Monitor

- Activates any hardwire or wireless alarm system if temperature falls below 39°F (4°C)
- Very small size for unobtrusive appearance
- Requires no power to operate
- Perfect for homes, vacation properties or any unattended building



WINLAND
ELECTRONICS, INC.

SPECIFICATIONS

TA-40 TEMP°ALERT®

SPECIFICATION	VALUE
Contacts	Contact opening temperature $\leq 39.5^{\circ}\text{F} \pm 5.4^{\circ}\text{F}$ ($4^{\circ}\text{C} \pm 3^{\circ}\text{C}$)
Operating Temperature Range	32° to 100° F (0° to 38° C)
Contact Ratings	Voltage \leq to 24V AC/DC • Current \leq 200 mA
Recommended Sensor Cable	18 to 24 gauge
Case Material	ABS plastic rated 94V-0
Dimensions	2.5" x .8" x .55" (6.4 cm x 2 cm x 1.4 cm)
Weight	3 oz. (85 g)
Color	Off-white
Mounting	2 screw holes (.165" dia.)
Master Pack Weight	Carton of 12: 1 pound (.45 kg)
Warranty	1 year limited



WINLAND
ELECTRONICS, INC.

1950 Excel Drive
Mankato, MN 56001

1-800-635-4269
In MN: 507-625-7231
FAX: 507-387-2488

www.winland.com

©2006 Winland Electronics Inc.
D-011-0023 Rev. B